

Rubber Processing Oil

Aromatic - RPO

Speciality Oils & Lubricants

Aromatic type rubber processing oil conforming to ASTM 101 Type, formulated from specially selected aromatic extracts. It has good compatibility and suitable for use in NR, SBR, PBR, NBR, CR.Rubbers.

SR NO	TEST PARAMETERS	Unit	Test Method	TEST RESULTS	
2.	Color		ASTM D - 1500	8.0 (Typical) (Dark Brownish Black)	
3.	Density at 29.5° C	gm / ml	ASTM D – 1298	1.0 (Typical)	
4	Kinematic viscosity at 100° C	cSt	ASTM D – 445	18	28
5	Flash Point COC	°C	ASTM D - 92	220	
6	Pour Point, °C	°C	ASTM D – 97		+30
7	Aniline Point	°C	ASTM D – 611	25	50

APPLICATIONS: Aromatic Rubber Processing Oil is suitable for the following applications :

- Manufacturing of Automotive Tyre & Tube
- Tyre retreading
- Belting & Hoses
- Battery Containers
- All NR extruded products

Disclaimer: We makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the products for the application contemplated by the user is solely their responsibility.

Derlan Chemicals, Ahmedabad - 382480, India

Website: www.derlanchem.com, Email: info@derlanchem.com, export@derlanchem.com

Ph.: 0091-9687546102